



UNIVERSAL WATER BASED PRIMER

Ready to use water-based bitumen primer

Product description

UNIVERSAL WATER BASED PRIMER is produced on the base of bitumen dispersion in water; it does not contain solvents. The primer has a neutral smell, so it is perfectly suited for indoor works.

Area of application

Ready to use UNIVERSAL WATER BASED PRIMER is intended for preparation of the surface before installation of bitumen roofing and waterproofing materials. The prime coating is necessary for ensuring the strong adhesion of the bitumen-based waterproofing materials to porous, rough and dusty surfaces.



Main characteristics

Properties	Performance
Content of bitumen with emulsifier, %	25-40
Drying time at 20°C, h	≤ 1
Relative viscosity (nozzle diameter 4 mm), s	5-30
Softening temperature, °C	≥ 80
Consumption, l/m ²	0.25-0.35
Bucket volume, l	20

Performance of works

UNIVERSAL WATER BASED PRIMER is applied to a surface by roller, large or small brush. Ready to use primer is applied to the base at once that grants additional convenience and enhanced performance. Application temperature range is from +5°C to +40°C.

More details on installation are given in the relevant manuals of TECHNOL Corporation.

NOTE: Avoid contact with skin and eyes.

Storage

The product should be stored in a dry place protected from direct sunlight at temperatures from +5°C. Shelf life – 6 months.

Packaging Information

Metal eurobuckets of 20 l.