



UNIVERSAL WATER BASED PRIMER (Primer TECHNOMICOL No.04)

TU 5775-006-72746455-2007

Product description

UNIVERSAL WATER BASED PRIMER is produced on the base of bitumen dispersion in water; it does not contain solvents. The primer has a neutral smell, so it is perfectly suited for indoor works.

Area of application

Ready to use UNIVERSAL WATER BASED PRIMER is intended for preparation of the surface before installation of torched-on or self-adhesive waterproofing material. The prime coating is necessary for ensuring the strong adhesion of the bitumen-based waterproofing materials to porous, rough and dusty surfaces.



Main characteristics

Indicator name	Unit	Value	Testing method
Content of bitumen with emulsifier	%	25-40	GOST R 52128
Softening point	°C	≥75	GOST R 52128
Relative viscosity	s	5-30	GOST R 52128
Drying time at 20°C	h	1	TU 5775-007-72746455-2007

Performance of works

According to the General Guidelines for design and construction of roofs with polymer-bitumen torch-on materials of TECHNOMICOL Corporation, the Guidelines for the waterproofing of underground structures of TECHNOMICOL Corporation.

UNIVERSAL WATER BASED PRIMER is applied to a surface by roller, large or small brush. Ready to use primer is applied to the base at once that grants additional convenience and enhanced performance. Application temperature range is from +5°C to +40°C.

Primer consumption – 0.25-0.35 l/m². Drying time under standard conditions is not more than 1 hour.

NOTE: Avoid contact with skin and eyes.

Storage

The product should be stored in a dry place protected from direct sunlight at temperatures from +5°C. Shelf life – 6 months.

Packaging Information

Metal eurobuckets of 20 l.