



## NICOBAND



NICOBAND sealant tape a convenient way to seal various cracks and joints. Can also be used to insulate junctions, for roofing repairs and for roof repair systems. The special UV protection layer increases its service life outdoors and the assortment of colors makes it suitable for any roof.

### ■ ADVANTAGES:

- Protected from UV radiation.

The bitumen layer of NICOBAND sealant tape is protected from UV radiation by aluminum coating. This makes it possible to use the tape outdoor.

- Easy to use and durable.

NICOBAND sealant tape is very easy to use and its application requires no special skills. The sealing function of the tape extends for its full lifetime (10 years) thanks to specially formulated polymer-bitumen binder.

- Different colors.

The tape is designed for the most popular roofing colors (including metallic). It allows to perform repairs or maintenance in the tone of the main surface without disturbing its form.



- Flawless adhesion to many different surfaces.

Self-adhesive layer provides perfect quality adhesion to many different surfaces: metal, slate, wood, plastic, plaster, concrete, glass, etc.



### ■ METHOD OF APPLICATION:

The surface must be flat, dry and clean. Cut the tape to required length, remove the protective film, stick the tape to desired area and press it firmly. If the temperature is below +5°C it is necessary to first keep NICOBAND in room temperature for at least 12 hours before application. The use of the material at sub-zero temperatures requires additional heating of the surface.

The use of NICOBAND is not recommended on hot vertical surfaces or on surfaces with a temperature above +80°C.



WIDTH, cm	5	7.5	10	15	20	30
Length 3 m	+	+	+	+	-	-
Length 10 m	-	+	+	+	+	+

TAPE DIMENSIONS, mm	PACKAGE SIZE, mm	QUANTITY IN PACKAGE	WEIGHT OF PACKAGE, kg
3000x50	box 240x240x320	24	5.9
3000x75	box 240x240x320	16	5.9
3000x100	box 240x240x320	12	5.9
3000x150	box 240x240x320	8	5.9
10000x75	box 180x180x320	4	5
10000x100	box 180x180x320	3	5
10000x150	box 180x180x320	2	5
10000x200	box 180x180x320	1	3.5