



BITUMEN PRIME COATING

Ready to use solvent-based bitumen primer

Product description

BITUMEN PRIME COATING presents a mix of high-quality bitumen and specially selected organic solvents. The primer has a good covering capacity and penetrability.

Area of application

Ready to use BITUMEN PRIME COATING is intended for preparation of the surface before installation of bitumen roofing and waterproofing materials. The prime coating is necessary for ensuring the strong adhesion of the bitumen-based waterproofing materials to porous, rough and dusty surfaces.



Main characteristics

Properties	Performance
Mass fraction of non-volatile substances, %	45-55
Drying time at 20°C, h	≤ 12
Relative viscosity (nozzle diameter 4 mm), s	15-40
Softening temperature, °C	≥ 80
Consumption, l/m ²	0.25-0.35
Bucket volume, l	3, 10, 20

Performance of works

BITUMEN PRIME COATING is applied to a surface by roller, large or small brush. Ready to use primer is applied to the base at once that grants additional convenience and enhanced performance. Application temperature range is from -20°C to +40°C. At a temperature below +5°C keep the primer in a warm room for at least 24 hours.

More details on installation are given in the relevant manuals of TECHNOMICOL Corporation.

NOTE: Do not use near an open flame. Work in well-ventilated areas. Avoid contact with skin and eyes.

Storage

The product should be stored in a dry place protected from direct sunlight at temperatures from -20°C to +30°C. Shelf life – 18 months.

Packaging information

Metal eurobuckets of 3, 10 and 20 l.